

AUDIOMETRIC BOOTHS Double-Wall Audiometric Examination Suites

ETS-Lindgren's Double Wall Exam Suites are soundproof booths constructed with our premium AS-A504 10 cm (4 in) thick double wall panels for maximum isolation.



ETS-Lindgren's Double Wall Exam Suites are soundproof booths constructed with our premium AS-A504 10 cm (4 in) thick double wall panels for maximum isolation. They feature true double door design; one in-swing, one out-swing.

For installation convenience, the ventilation silencer can be mounted on either roof or wall depending on space constraints and sound booth size.

These audiometric suites offer the choice of either a standard model package or a built-to-order design to meet special requirements. Please contact ETS-Lindgren for further information.

Key Features

- Double Wall Design, AS-A504 10 cm (4 in) Thick Panels
- Pre-wired acoustically Sealed Cable Jack Panel
- Rough in for Alert Device Cable Access
- Low Profile 12.07 cm (4 3/4 in) Acoustic and Vibration Isolated Floor System, Control and Exam Sides
- Ceiling Mounted LED Lighting
- Acoustically Engineered Ventilation System
- Extended Roof Apron Trim, 20.32 cm (8 in) Above the Roof of the Booth
- SoundSecure™ Patient Observation Window
- Carpeting with Cove Base Trim
- Hospital Grade Recessed Electrical Devices
- UL Classified Power Panels

Specifications

Physical Specifications

Model	Control Interior	Exam Interior	Overall Exterior	Weight
RS-242	122 cm W x 193 cm L x 198 cm H (4 ft 0 in x 6 ft 4 in x 6 ft 6 in)	183 cm W x 193 cm L x 198 cm H (6 ft 0 in x 6 ft 4 in x 6 ft 6 in)	396 cm W x 254 cm L x 269 cm H (13 ft 0 in x 8 ft 4 in x 8 ft 10 in)	5,488 kg (12,100 lb)
RS-242L	152 cm W x 193 cm L x 198 cm H (5 ft 0 in x 6 ft 4 in x 6 ft 6 in)	183 cm W x 193 cm L x 198 cm H (6 ft 0 in x 6 ft 4 in x 6 ft 6 in)	427 cm W x 254 cm L x 269 cm H (14 ft 0 in x 8 ft 4 in x 8 ft 10 in)	5,660 kg (12,480 lb)
RS-243	163 cm W x 213 cm L x 198 cm H (5 ft 4 in x 7 ft 0 in x 6 ft 6 in)	224 cm W x 213 cm L x 198 cm H (7 ft 4 in x 7 ft 0 in x 6 ft 6 in)	478 cm W x 274 cm L x 269 cm H (15 ft 8 in x 9 ft 0 in x 8 ft 10 in)	6,332 kg (13,960 lb)
RS-244	217 cm W x 254 cm L x 198 cm H (7 ft 0 in x 8 ft 4 in x 6 ft 6 in)	274 cm W x 253 cm L x 198 cm H (9 ft 0 in x 8 ft 4 in x 6 ft 6 in)	579 cm W x 315 cm L x 269 cm H (19 ft 0 in x 10 ft 4 in x 8 ft 10 in)	7,956 kg (17,540 lb)
RS-245	244 cm W x 284 cm L x 198 cm H (8 ft 0 in x 9 ft 4 in x 6 ft 6 in)	305 cm W x 284 cm L x 198 cm H (10 ft 0 in x 9 ft 4 in x 6 ft 6 in)	640 cm W x 345 cm L x 269 cm H (21 ft 0 in x 11 ft 4 in x 8 ft 10 in)	9,008 kg (19,860 lb)
RS-246	152 cm W x 157 cm L x 198 cm H (5 ft 0 in x 5 ft 2 in x 6 ft 6 in)	244 cm W x 157 cm L x 198 cm H (8 ft 0 in x 5 ft 2 in x 6 ft 6 in)	488 cm W x 218 cm L x 269 cm H (16 ft 0 in x 7 ft 2 in x 8 ft 10 in)	5,661 kg (12,480 lb)
RS-247	157 cm W x 244 cm L x 198 cm H (5 ft 2 in x 8 ft 0 in x 6 ft 6 in)	157 cm W x 244 cm L x 198 cm H (5 ft 2 in x 8 ft 0 in x 6 ft 6 in)	406 cm W x 218 cm L x 269 cm H (13 ft 4 in x 7 ft 2 in x 8 ft 10 in)	5,752 kg (12,680 lb)
RS-248	157 cm W x 244 cm L x 198 cm H (5 ft 2 in x 8 ft 0 in x 6 ft 6 in)	305 cm W x 244 cm L x 198 cm H (10 ft 0 in x 8 ft 0 in x 6 ft 6 in)	554 cm W x 305 cm L x 269 cm H (18 ft 2 in x 10 ft 0 in x 8 ft 10 in)	7,657 kg (16,880 lb)

Please Note: Exterior height includes roof mounted ventilation system. Other options are available if host space cannot accommodate overall height. Please allow a minimum of 10 cm (4 in) clearance between booth and host walls
