

MA 1

Air Conduction Audiometer

Smallest handheld portable air-conduction audiometer.

Features At a Glance

- Portable air conduction screener (500Hz, 1K, 2k, 4KHz)
- Battery operated (2AA alkaline)
- Easy one hand push button operation
- Exceptionally lightweight, only 1 pound
- Carrying case included

Sleek, Small Design

With its super-lightweight design, the MA 1 is small enough to hold in the palm of your hand. Tucked into its carrying case (included) the MA 1 is our smallest, lightest portable audiometer. Although it is small, it offers a full range of screening.

Accurate, Dependable Engineering

Because it's portable, the MA 1 is engineered to be tough and reliable. Take the MA 1 anywhere with confidence. Its user-friendly push button design makes adjusting frequency and intensity easy.



Technical Data

Test Frequencies	500, 1000, 2000, 4000 Hz
Rise/Fall Time	35 msec typical
Attenuator Range	15 to 50 db _{HL} 5 db steps
Distortion	0.5% THD typical, 3% THD maximum
Stimulus	Continuous
Dimensions	2.5 in x 6 in x 7/8 in
Weight	2.1 lbs
Power Supply	Battery operated (2 AA alkaline)

STANDARD ACCESSORIES

- DD45 headphones with DH7 headband
- Carrying Case
- Operation Manual

Specifications subject to change without notice.

Standard Components



Carrying Case



DD45 headset with HB7 headband



MA 1 Handheld Device

MAICO Diagnostics

10393 West 70th Street
Eden Prairie, MN 55344, USA

Tel.: (888) 941-4201
Fax: (952) 903-4100

info@maico-diagnostics.com
www.maico-diagnostics.com/us

ONE YEAR LIMITED WARRANTY: This warranty is extended to the original purchaser of the instrument, by MAICO, through the Distributor from whom it was purchased. The warranty covers defects in material and workmanship for a period of one year from date of invoice of the instrument to the original purchaser. Accessories which are purchased from MAICO at the same time as the instrument are also under warranty for one year from the date of invoice. For additional information contact your MAICO Distributor.